



Application:

1. Face to face is according to BS5150,
2. Flange drilled is according to BS4504 PN16,
3. The working pressure PN16.

Nos.of hole	4	4	8	8	8	8	12	12	12
Dia.of hole	18	18	18	18	18	22	22	26	26
C	178	178	203	245	254	305	356	405	457
K	125	145	160	180	210	240	295	355	410
g	102	122	138	158	188	212	268	320	378
D	165	185	200	220	250	285	340	405	460
H	310	345	400	457	540	610	822	935	1090
L	178	190	203	229	254	267	292	330	356
(mm)	2"	2½"	3"	4"	5"	6"	8"	10"	12"

17	SEAT RING	SS
16	DISC RING	SS
15	GASKET	NBR
14	PACKING	Ys450F
13	GLAND	A126
12	NUT	BRASS
11	STEM NUT	BRASS
10	BOLT	A3
9	DISC	Cast iron
8	BODY	Cast iron
7	BOLT	A3
6	NUT	A3
5	BONNET	Cast iron
4	"T" BOLT	A3
3	YOKE	A126
2	HANDWHEEL	Cast iron
1	STEM	STAINLESS STEEL
NO:	NAME	MATERIAL

MechTech Valve Services The Stenders, Mitcheldean Gloucestershire GL17 0ZE Tel:01594 541717 www.mechtechvalveservices.com						
MVS 182	BS5150 OS&Y GATE VALVE					